Copyright © 2016 Aleph Objects, Inc.
Permission is granted to copy, distribute and/or modify this document under the terms of the Creative Commons Attribution 4.0 International Public License (CC BY-SA 4.0). 11 links 20mm Cable Chain [EL-MS0379] 20mm Inner Width Mounting Brackets (male and female) – [EL-MS0382] 28mm Bend Radius \* use shown orientation Female end Male end 1x [EL-MS0259] Heat Shrink Tubing 70mm 1x [EL-MS0343] 1x [PC-CN0032] Term Block Plug Bed pwr 2POS 1x [PC-CN0001] Female 2pin Housing Y max 3x [PC-CN0003] Y min Female 3pin Housing **\*\*\*\*\*\*\*** Pin 3 Pin 2 Pin 4 1x [EL-MS0073] 1/4" Black Panduit Pin 6 Length = 350mm 1x [EL-MS0247] BLACK Shrink Tubing 3x [EL-MS0062] Female 4pin Housing Pin 1 ▶ Pin 1 Pin 4

1x [EL-MS0073] 1/4" Black Panduit

Length = 460mm

1x [EL-MS0073] 1/4" Black Panduit Length = 140mm

1x [EL-MS0434] RED Shrink Tubing

25mm

▶Pin 1

Pin 2

Pin 3

Pin 4

**\*\*\*\*\*\*\*\*\*** 

Pin 6

Pin 3

Pin 4

Pin 6

±3.175mm/0.3048m ±1.04166% Cut Tolerance:

LULZBOT

Gladiola		ALEPH	
DRAWN BY E N Kuzmenko	DATE 08/04/2016	OBJECT: INCORPORATE	
CHECKED BY MIC	DATE 09/22/2016	Bed Harn	ess
EL-HR0114		FILE NAME bed_harnesses	SHEET 1

Rev	Date	Changes
G	08/26/2016	-Shorten right-side of Y-motor shielding by 5mm -Use fork terminal on right-side of Y-motor shielding -Separate left-side Z shielding -Use Red and Black heat shrink on Z motor wires