

FOR 6 mm BELTS
 MOLDED WITH INSERT
 DOUBLE FLANGE

TRUE METRIC® PROFILE



0 10




> MATERIAL:

Pulley - Polycarbonate, Fiberglass Reinforced
Insert - Brass, Knurled

> SPECIFICATIONS:

Pulleys with 36 & 40 grooves do not have webs.
 Pulleys with:
 5 & 6 mm bore have M3 set screw & spot drill.
 8 mm bore have M4 set screw & spot drill.



METRIC COMPONENT

Catalog Number	No. of Grooves	P.D.	D Dia.	D ₁ Dia.	d Bore H9	d Tolerance
A 6Z51M036DF0605	36	23	22.4	28	5	+0.030/0
A 6Z51M036DF0606	36	23	22.4	28	6	+0.030/0
A 6Z51M036DF0608	36	23	22.4	28	8	+0.036/0
A 6Z51M040DF0605	40	25.5	25	30	5	+0.030/0
A 6Z51M040DF0606	40	25.5	25	30	6	+0.030/0
A 6Z51M040DF0608	40	25.5	25	30	8	+0.036/0
A 6Z51M042DF0605	42	26.7	26.2	31	5	+0.030/0
A 6Z51M042DF0606	42	26.7	26.2	31	6	+0.030/0
A 6Z51M042DF0608	42	26.7	26.2	31	8	+0.036/0
A 6Z51M044DF0605	44	28	27.5	33	5	+0.030/0
A 6Z51M044DF0606	44	28	27.5	33	6	+0.030/0
A 6Z51M044DF0608	44	28	27.5	33	8	+0.036/0
A 6Z51M048DF0605	48	30.6	30.1	35	5	+0.030/0
A 6Z51M048DF0606	48	30.6	30.1	35	6	+0.030/0
A 6Z51M048DF0608	48	30.6	30.1	35	8	+0.036/0
A 6Z51M060DF0606	60	38.2	37.7	43	6	+0.030/0
A 6Z51M060DF0608	60	38.2	37.7	43	8	+0.036/0
A 6Z51M065DF0606	65	41.4	40.9	46	6	+0.030/0
A 6Z51M065DF0608	65	41.4	40.9	46	8	+0.036/0
A 6Z51M072DF0606	72	45.8	45.3	51	6	+0.030/0
A 6Z51M072DF0608	72	45.8	45.3	51	8	+0.036/0
A 6Z51M080DF0606	80	50.9	50.4	56	6	+0.030/0
A 6Z51M080DF0608	80	50.9	50.4	56	8	+0.036/0
A 6Z51M090DF0606	90	57.3	56.8	63	6	+0.030/0
A 6Z51M090DF0608	90	57.3	56.8	63	8	+0.036/0
A 6Z51M100DF0606	100	63.7	63.2	69	6	+0.030/0
A 6Z51M100DF0608	100	63.7	63.2	69	8	+0.036/0
A 6Z51M110DF0606	110	70	69.5	75	6	+0.030/0
A 6Z51M110DF0608	110	70	69.5	75	8	+0.036/0
A 6Z51M120DF0606	120	76.4	75.4	82	6	+0.030/0
A 6Z51M120DF0608	120	76.4	75.4	82	8	+0.036/0
A 6Z51M130DF0606	130	82.8	82.3	88	6	+0.030/0
A 6Z51M130DF0608	130	82.8	82.3	88	8	+0.036/0