



Model: LulzBot Mini 1.0 3D Printer

Serial Number:	
Date Completed:	
Tested by:	

Configuration:

Electronics:	Mini-RAMBo 1.1b
Firmware:	Marlin for Mini 2015-Q4
Nozzle:	0.5mm diameter nozzle
Settings:	

Stepper Motor	Steps/mm	Max Length	Microstep Mode	Digipot
X	100.5	155	16	175
Y	100.5	155	16	175
Z	1600	155	16	220
E0	833	NA	16	135

Z Offset

General:

- □ Are all the screws and zip ties tight?
- □ Are the current version of parts being used?
- □ Is the Spool Mount properly mounted so it flips up and sits securely?
- □ Is the Finger Clip properly mounted with the taller side on the left?
- □ Are the switches installed securely?
- □ Are all 4 rubber feet installed?
- □ Is the PEI tape free of bubbles and wrinkles?
- □ Is the heat bed adhesive smooth and consistent?
- □ Is the frame free of scratches and scuffs?

Y Axis:

- Does the Y bed move freely back and forth?
- □ Is the Y bed tight side to side from motion and twisting?
- Does the Y belt rub on the y-idler by the bearings?
- Are the Y pulley set screws tight with one aligned with the flat on the motor shaft?
- □ Is the Y belt tight?
- □ Are the four bed leveling washers tight?
- □ Are the belts trimmed far enough to not interfere with the pulley or bearing?



QUALITY ASSURANCE RECORD



X Axis:

- □ Are the X pulley set screws tight with one aligned with the flat on the motor shaft?
- Does the X belt rub on the x-idler by the bearings?
- Does the X belt rub on the screw heads of the belt mount?
- □ Is the X belt tight?
- Does the X axis move freely end to end?
- Are the belts trimmed far enough to not interfere with the pulley or bearing?
- □ Are the wires and zip ties behind the carriage free from touching the case wall?

Z Axis:

- Do the Z drive rods rotate smoothly?
- □ Are the coupler set screws tight?
- □ Are the drive rods and motor shafts aligned so the couplers are not bent?

Extruder:

- □ Are the extruder springs set to 8mm between the cap and the latch?
- □ Are the V grooves on the extruder gears lined up?
- □ Is the hobbing aligned to the hole in the extruder?
- □ Can you feed filament about 100mm from the top of the extruder?

Electronics:

- □ Are all connections to the Mini-Rambo plugged in correctly?
- □ Are all cables free from contacting any moving parts?

Test and Verification Results:

- □ Verify case fan is running.
- □ Verify extruder blower is running.
- □ Verify control of the extrusion fan.
- Nozzle temperature control verified.
- □ Extruder control verified.
- **I** X, Y, and Z min and max stop switches verified.
- □ Bed leveling is functioning properly.
- □ Bed temperature control verified.
- □ Bearing conditioning complete.
- □ Test print (Octopus*) successful.
- □ Print head moved to shipping position.

*Octopus by yeoldbrian is licensed under CC BY-SA 4.0

