



FCC Part 15 Subpart B Class B
Verification Test Report
Industry Canada ICES-003 Test Report
Regarding Emissions Compliance of the
Aleph Objects
TAZ Workhorse 3D Printer

In Accordance with the Emissions Standards
FCC's Title 47 CFR Part 15 Subpart B Class B
ICES-003 Information Technology Equipment Class B

Revision History

Release	Date	Description
1.0	28 June 2019	Initial release

Description of Equipment Under Test (EUT)

Test Item : TAZ Workhorse 3D Printer
Manufacturer : Aleph Objects, Inc.

Manufacturer's information

Manufacturers
Representative : Mark Pelletier - Engineer
Company : Aleph Objects, Inc.
Address : 626 West 66th Street
Loveland, Colorado 80538
U.S.A.
Website : <https://www.alephobjects.com/index.html>

Tests Performed at

Address : EMI Test Lab LLC
1822 Skyway Drive Unit J
Longmont, Colorado 80504
U.S.A
Website : <http://www.emitestlab.com/>

Test Specifications : FCC Part 15 Subpart B Class B, ICES-003 Class B
Tests completed : 28 May 2019

Result of Testing : **The EUT is in Compliance with FCC Part 15 Class B for home use. The EUT also meets ICES-003 Class B (Canada)**

Senior EMC Engineer : Dennis King



Report written by : Dennis King – EMI Test Lab
Test Plan : Dennis King and Mark Pelletier for Aleph Objects
Report date : 28 June 2019

These test results relate only to the specific unit that was tested. A periodic production audit to verify continued compliance is recommended.

Table of Contents

- 1. General Test Information.....page 4
 - 1.1. Applied Standards
 - 1.2. Detailed description of test configuration, input and output ports
 - 1.2.1. Description of test configuration
 - 1.2.2. Description of input and output ports and power supply information
 - 1.2.3. Operating modes

- 2. Emissions.....page 9
 - 2.1. AC Mains conducted emissions
 - 2.2. Enclosure radiated emissions
 - 2.2.1. 30-1,000 MHz
 - 2.2.2. 1-6 GHz

- 3. Modificationspage 23

- 4. User Guide statements and labelspage 24

- 5. Test equipment.....page 28

- 6. Measurement Uncertainty.....page 30

- 7. Test Planpage 32

- 8. Conclusionpage 33

1 General

1.1 Applied Standards

The TAZ Workhorse was evaluated for emissions using the FCC's Title 47 CFR Part 15 Subpart B Class B for home use and Industry Canada's ICES-003 Issue 6 Class B.

The following documents were also used as guidance for testing;

- (a) Canadian Standards Association Standard CAN/CSA-CISPR 22-10(R2014), *Information technology equipment — Radio disturbance characteristics — Limits and methods of measurement*
 - This is an adoption with Canadian deviations of the identically titled IEC (International Electrotechnical Commission) Standard CISPR (International Special Committee on Radio Interference) 22, Sixth edition, 2008-09.
- (b) ANSI C63.4-2014, *American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz*, 2014

1.2 Detailed description of the test configuration, input and output ports

Test Configuration Definition:


The 3D Printer was tested while running test code that simulates a worst case for operation of the printer. The heater bed was on during all the testing.

Test code used is called TEST_2.gcode

All testing was done at 120 VAC 60 Hz, the nominal North American voltage and frequency.

Taz Workhorse Software:

The default software for the TAZ WORKHORSE 3D printer is called Cura LulzBot Edition. Cura is a Free Software program that both prepares your files for printing (by converting your model into GCODE), and also allows you to control the operation of your LulzBot 3D printer.



Typical screen shot of software used during emissions and immunity testing.



The Taz Workhorse – 3D Printer

<https://www.lulzbot.com/store/printers/lulzbot-taz-workhorse>

1.2.1 Description of test configuration

EUT : TAZ WORKHORSE 3D Printer
 Manufacturer : Aleph Objects, Inc.
 System model name : TAZ WORKHORSE
 Serial Number : WH001
 Test Voltage : 120 VAC 60 Hz

1.2.2. Description of tested input and output ports and power supply information

Number of cable type	Type of Cable	From	To	Shielded?	Remarks - length
1	USB	unterminated	Taz Workhorse	Yes	6 ft. Tripp Lite model: U023-006 – ferrites on both ends

Power supply location	Manufacturer	Model	Serial number	Shielded	Remarks
Internal AC supply	Meanwell	RSP-500-24	Not available	Shielded enclosure	UL and TUV Rheinland Certified – Output; 24V 21A

1.2.3 Operation modes

The Equipment Under Test (EUT) was set up and operated as described in section 1.2.

During preliminary testing for emissions it was determined that the following configurations are worst case for emissions and immunity. All further testing was done in these modes.

The 3D Printer was tested while running test code that continuously moves the print heads and heats the heater bed.

The 3D Printer was checked while printing from the SD Card and also while operated from a laptop connecting to the printer through a USB cable that is supplied with the unit.

All testing was done at 120 VAC 60 Hz, the nominal North American voltage and frequency.

2 Emissions


The EUT (equipment under test) has been tested to determine conformity with the relevant emissions parts of the FCC's Title 47 CFR Part 15 Subpart B Class B for home or commercial use - section 15.107 for conducted and section 15.109 for radiated - and ICES-003 Issue 6 Class B for Canada.

AC Power line conducted and radiated field strength measurements concerning the emission of radiated and conducted electromagnetic disturbances were made.


2.1 AC Mains Power Input Ports

The disturbance voltage emissions levels at the AC mains power port of the EUT were measured in conformity with and according to the criteria as stated below.


Basic standard	:	FCC Part 15, Subpart B, ICES-003 Issue 6
Test method	:	ANSI C63.4-2014, CAN/CSA – CISPR 22-10
Frequency range 1	:	0.15 – 0.5 MHz
Limit	:	66 dBuV quasi peak, 56 dBuV average Decreasing with the log of frequency to range 2
Frequency range 2	:	0.5 – 5 MHz
Limit	:	56 dBuV quasi peak, 46 dBuV average
Frequency range 3	:	5 – 30 MHz
Limit	:	60 dBuV quasi peak, 50 dBuV average

Results of the measurements concerning the emissions of voltage levels at the AC mains input port of the EUT.	<u>PASS Class B for home or commercial use</u>
Name of Test Engineer:	Dennis King
Signature:	
Date:	27 May 2019
<p>Remarks. The EUT is plugged into the LISN powered at 120 VAC 60 Hz.</p> <p><u>Conducted Emission Summary:</u></p> <p>The EUT passes both the quasi peak and the average limits. PASS</p>	

Peak Data – Line - usb connected to laptop
see the following page for passing quasi peak data




Quasi Peak Data – Line – usb connected to laptop




Frequency (MHz)	QP Disturbance (dBuV)	QP Limit	EUT--Line QP	Tranducer Connection	Correction Factor (dB)
0.150	34.60	66.00	31.40	AMN	0.20
1.620	39.47	56.00	16.53	AMN	0.92
1.850	39.48	56.00	16.52	AMN	0.93
1.790	40.73	56.00	15.27	AMN	0.93
7.820	33.41	60.00	26.59	AMN	1.13
13.260	30.31	60.00	29.69	AMN	1.25
0.204	55.12	64.45	9.33	AMN	0.22
0.272	50.43	62.53	12.09	AMN	0.23
0.339	42.65	60.60	17.95	AMN	0.25

Peak Data – Neutral – usb connected to laptop - see the following page for passing quasi peak data




Quasi Peak Data – Neutral – usb connected to laptop




Frequency (MHz)	QP Disturbance (dBuV)	QP Limit	EUT--Line QP	Tranducer Connection	Correction Factor (dB)
0.150	34.90	66.00	31.10	AMN	0.20
0.270	42.79	62.57	19.78	AMN	0.23
1.620	39.36	56.00	16.64	AMN	0.92
1.790	40.44	56.00	15.56	AMN	0.93
1.790	40.34	56.00	15.66	AMN	0.93
13.130	29.63	60.00	30.37	AMN	1.25
0.204	57.58	64.46	6.88	AMN	0.22

Peak Data – Line – running from sd card - see the following page for passing quasi peak data




Quasi Peak Data – Line – running from sd card




Frequency (MHz)	QP Disturbance (dBuV)	QP Limit	EUT--Line QP	Tranducer Connection	Correction Factor (dB)
0.150	36.60	66.00	29.40	AMN	0.20
0.270	43.11	62.57	19.46	AMN	0.23
0.270	43.03	62.57	19.54	AMN	0.23
7.740	28.42	60.00	31.58	AMN	1.12
16.560	28.60	60.00	31.40	AMN	1.30
16.800	30.40	60.00	29.60	AMN	1.30
0.338	40.15	60.63	20.47	AMN	0.25
0.273	50.24	62.49	12.25	AMN	0.24


Peak Data – Neutral – running from sd card - see the following page for passing quasi peak data




Quasi Peak Data – Neutral – running from sd card



Frequency (MHz)	QP Disturbance (dBuV)	QP Limit	EUT--Line QP	Tranducer Connection	Correction Factor (dB)
0.150	36.90	66.00	29.10	AMN	0.20
7.820	29.64	60.00	30.36	AMN	1.13
12.190	28.53	60.00	31.47	AMN	1.23
16.680	29.00	60.00	31.00	AMN	1.30
0.203	44.82	64.48	19.66	AMN	0.22
0.272	49.63	62.53	12.89	AMN	0.23
0.339	40.75	60.59	19.83	AMN	0.25



Conducted emissions test setup – connected through usb cable




Conducted emissions test setup – running from sd card

2.2 Enclosure

2.2.1 30-1,000 MHz

The radiated field strength levels (electric component) have been measured in conformity with and according to the criteria as stated below.


Basic standard	:	FCC Part 15, Subpart B, ICES-003 Issue 6
Test method	:	ANSI C63.4-2014, CAN/CSA – CISPR 22-10
Limit distance	:	3 meters
Frequency range 1	:	30 -230 MHz
Limits	:	40 dBuV/m
Frequency range 2	:	230 – 1,000 MHz
Limits	:	47 dBuV/m

Results of the measurements concerning radiated electromagnetic fields (electric component) emitted by the EUT, enclosure, as a tested system	<u>PASS Class B for home or commercial use</u>
Name of Test Engineer:	Dennis King
Signature:	
Date:	24 May 2019
<u>Radiated Emissions Summary:</u>	PASS Class B
Remarks: 120 VAC 60 Hz	
Max frequency or data rate is less than 108 MHz	

The chart below is peak data compared to a quasi-peak limit –

connected through the usb cable to a laptop


See the Quasi peak data for passing results



The above chart is corrected peak data;

Spectrum Analyzer reading + Cable loss + Antenna Factor – pre-amp gain

The chart below is quasi peak data compared to a quasi-peak limit
connected through the usb cable to a laptop



The above chart is corrected quasi peak data;
Spectrum Analyzer reading + Cable loss + Antenna Factor – pre-amp gain

Quasi Peak Data


connected through the usb cable to a laptop

EMI Test Lab						Sheet4
Frequency	Field Strength EUT	Limit	Azimuth	Height	Antenna Polarization	Delta from the Limit
(MHz)	(dBuV/m)	(dBuV/m)	Degrees	meters	H or V	dB micro volts
83.63	15.66	40	92.0	1.4	V	-24.34
226.36	22.79	40	148.0	1.4	V	-17.21
205.44	29.08	40	280.0	1.4	V	-10.92
149.10	22.11	40	304.0	1.4	V	-17.89
199.00	27.33	40	348.0	1.4	V	-12.67
984.45	30.65	47	0.0	1.4	H	-16.35
142.86	23.55	40	4.0	1.4	H	-16.45
147.38	28.80	40	48.0	1.4	H	-11.2
204.36	28.11	40	84.0	1.4	H	-11.89
224.05	31.80	40	108.0	1.4	H	-8.2
194.25	34.44	40	140.0	1.4	H	-5.56
990.89	31.91	47	152.0	1.4	H	-15.09
998.83	31.61	47	156.0	1.4	H	-15.39
955.99	35.40	47	232.0	1.4	H	-11.6
250.04	29.16	47	268.0	1.4	H	-17.84
205.61	25.85	40	280.0	1.4	H	-14.15
234.09	31.50	47	284.0	1.4	H	-15.5
210.39	31.67	40	288.0	1.4	H	-8.33

The chart below is peak data compared to a quasi-peak limit –

Running from the SD Card

See the Quasi peak data for passing results




The above chart is corrected peak data;

Spectrum Analyzer reading + Cable loss + Antenna Factor – pre-amp gain

The chart below is quasi peak data compared to a quasi-peak limit

Running from the SD Card



**The above chart is corrected quasi peak data;
Spectrum Analyzer reading + Cable loss + Antenna Factor – pre-amp gain**

Quasi Peak Data


Running from the SD Card


EMI Test Lab						Sheet4
Frequency	Field Strength EUT	Limit	Azimuth	Height	Antenna Polarization	Delta from the Limit
(MHz)	(dBuV/m)	(dBuV/m)	Degrees	meters	H or V	dB micro volts
31.78	18.86	40	28.0	1.4	V	-21.14
226.38	21.17	40	148.0	1.4	V	-18.83
220.96	22.74	40	156.0	1.4	V	-17.26
150.36	17.43	40	164.0	1.4	V	-22.57
86.40	15.38	40	168.0	1.4	V	-24.62
200.19	26.69	40	188.0	1.4	V	-13.31
192.61	22.30	40	12.0	1.4	H	-17.7
149.55	23.87	40	12.0	1.4	H	-16.13
146.43	25.00	40	24.0	1.4	H	-15
231.44	30.69	47	68.0	1.4	H	-16.31
228.10	28.45	40	148.0	1.4	H	-11.55
204.15	23.60	40	212.0	1.4	H	-16.4
138.98	18.50	40	304.0	1.4	H	-21.5
172.98	21.74	40	308.0	1.4	H	-18.26
226.28	34.67	40	348.0	1.4	H	-5.33

2.2.2 1 – 40 GHz

The radiated field strength levels (electric component) have been measured in conformity with and according to the criteria as stated below.

Basic standard	:	FCC Part 15, Subpart B, ICES-003 Issue 6
Test method	:	ANSI C63.4-2014, CAN/CSA – CISPR 22-10
Limit distance	:	3 meters
Frequency range	:	1-40 GHz
Limits	:	Average 54 dBuV/m, Peak 74 dBuV/m


Results of the measurements concerning radiated electromagnetic fields (electric component) emitted by the EUT, enclosure, as a tested system	<u>Not Required</u> <u>Highest frequency clock is less than 108 MHz</u>
<p style="text-align: right;">Name of Test Engineer:</p> <p style="text-align: right;">Signature:</p> <p style="text-align: right;">Date:</p>	<p>Dennis King</p>  <p>27 May 2019</p>
<p>Remarks: The highest frequency clock is < 108 MHz. Not required data for information only.</p>	



3 meter limits

Frequency Range	Class A Limits		Class B Limits	
	FCC ^{Note 1}	CISPR	FCC	CISPR
1 – 3GHz	Avg 60dBuV/m Pk 80dBuV/m	Avg 56dBuV/m Pk 76dBuV/m	Avg 54dBuV/m Pk 74dBuV/m	Avg 50dBuV/m Pk 70dBuV/m
3 – 6GHz	Avg 60dBuV/m Pk 80dBuV/m	Avg 60dBuV/m Pk 80dBuV/m	Avg 54dBuV/m Pk 74dBuV/m	Avg 54dBuV/m Pk 74dBuV/m
6 – 40 GHz	Avg 60dBuV/m Pk 80dBuV/m	No requirement	Avg 54dBuV/m Pk 74dBuV/m	No requirement ^{Note 3}

Note 1: The limit above has been extrapolated from 10m (as detailed in FCC rules) to 3m. The 10m limits are 49.5dBuV/m for average and 69.5dBuV/m for peak.
 Note 2: **Pk** indicates the peak limit and **Avg** indicates the average limit. There are some differences in the specifications for the detectors used to make peak and average measurements between FCC/ANSI and CISPR standards.
 Note 3: Work is in progress to extend the frequency range to 18 GHz




Frequency Range	Class A Limits		Class B Limits	
	FCC ^{Note 1}	CISPR	FCC	CISPR
1 – 3GHz	Avg 60dBuV/m Pk 80dBuV/m	Avg 56dBuV/m Pk 76dBuV/m	Avg 54dBuV/m Pk 74dBuV/m	Avg 50dBuV/m Pk 70dBuV/m
3 – 6GHz	Avg 60dBuV/m Pk 80dBuV/m	Avg 60dBuV/m Pk 80dBuV/m	Avg 54dBuV/m Pk 74dBuV/m	Avg 54dBuV/m Pk 74dBuV/m
6 – 40 GHz	Avg 60dBuV/m Pk 80dBuV/m	No requirement	Avg 54dBuV/m Pk 74dBuV/m	No requirement <small>Note 3</small>

Note 1: The limit above has been extrapolated from 10m (as detailed in FCC rules) to 3m. The 10m limits are 49.5dBuV/m for average and 69.5dBuV/m for peak.
 Note 2: **Pk** indicates the peak limit and **Avg** indicates the average limit. There are some differences in the specifications for the detectors used to make peak and average measurements between FCC/ANSI and CISPR standards.
 Note 3: Work is in progress to extend the frequency range to 18 GHz



Test setup for Radiated Emissions - usb



Test setup for Radiated Emissions – SD Card



Test setup for Radiated Emissions – SD card – 1- 6 GHz Horn antenna

3.0 Modifications

No modifications were made during the testing.

4.0 User Guide Statements and labels

From the FCC's CFR Part 15 Subpart B

1.1 §15.105 Information to the user.

User Guide Statement

(a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

NOTE: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment under FCC rules.

(b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment under FCC rules.

§15.19 Labelling requirements.

(a) In addition to the requirements in part 2 of this chapter, a device subject to certification, or verification shall be labelled as follows:

(1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under part 73 of this chapter, land mobile operation under part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

(2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with part 15 of the FCC Rules for use with cable television service.

(3) All other devices shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

(4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

(5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

Canadian Label requirement

From ICES-003 Issue 6 Published: January 2016 Updated: June 2016

9. Labelling Requirements

The manufacturer, importer or supplier shall meet the labelling requirements set out in this section and in Notice 2014-DRS1003 for electronic labelling for every unit: (i) prior to marketing in Canada, for ITE manufactured in Canada and (ii) prior to importation into Canada, for imported ITE. Each unit of an ITE model shall bear a label (see below) that represents the manufacturer’s or the importer’s SDoC with Innovation, Science and Economic Development Canada’s ICES-003. This label shall be permanently affixed to the ITE or displayed electronically and its text must be clearly legible. If the dimensions of the device are too small or if it is not practical to place the label on the ITE and electronic labelling has not been implemented, the label shall be, upon agreement with Innovation, Information Technology Equipment (Including Digital Apparatus) — Limits and Methods of Measurement ICES-003 9 Science and Economic Development Canada, placed in a prominent location in the user manual supplied with the ITE. The user manual may be in an electronic format and must be readily available.

Innovation, Science and Economic Development Canada ICES-003 Compliance Label:

CAN ICES-3 (*)/NMB-3(*)

* Insert either “A” or “B” but not both to identify the applicable Class of ITE.

5.0 Test equipment and Environmental Conditions

All tests were conducted within parameters specified for each test, for example >30% humidity for ESD.

The lab temperature during all testing was between 70-72 degrees F.

All equipment used for testing has been calibrated or verified for cal using NIST traceable standards.

Each piece of test equipment has a cal verification procedure that is conducted before and after each test.

Table of Test Equipment

Equipment	Description and Test	Model	Serial number	Next cal due
EMC Compact Tester - Haefely	EFT, Surge, AC Dips and Interrupts	AXOS 5	185501	28 March 2020
HP Spectrum Analyzer	Used for Radiated and Conducted Emissions	8566B	2607A02760	3 June 2020
HP Quasi-Peak Adapter	Used for Radiated and Conducted Emissions	85650A	8574A00233	3 June 2020
HP/Agilent Spectrum Analyzer	Used for Radiated and Conducted Emissions	E7401A	US41110467	22 Jan 2021
HP/Agilent Spectrum Analyzer	Used for Radiated Emissions 1-22 GHz	8593E	3710A02875	9 Jan 2021
HP/Agilent Spectrum Analyzer	Used for Radiated and Conducted Emissions	E7401A	US40240440	9 Jan 2021
Com-Power transient Limiter	Conducted Emissions	HZ560	001	3 June 2020
RF Bay Pre-Amp	Radiated emissions – 100kHz to 10 GHz	LPA-10-20	0643	12 Dec 2019
GTEM	Radiated Emissions and Radiated Immunity	5317	9703-1209	25 April 2020 – Field Uniformity Cal per IEC 61000-4-20
3 Meter FAR – Fully Anechoic Room	Radiated Immunity and Emissions	N/A	FAR #1	15 October 2019 Field Uniformity per IEC/EN 61000-4-3 and Correlation data to GTEM
ComPower Horn Antenna	1-18 GHz – Radiated Immunity and Emissions	AH 118	071040	20 March 2020
Chase BiLog Antenna	Radiated Emissions and Immunity	CBL6111	1121	20 March 2020
Marconi Instruments – Signal Generator 10kHz – 2.7 GHz	Radiated Immunity	2031	1196061031	20 October 2019
HP Signal Generator	Radiated Immunity	8657A	STD0578	3 May 2020

Test Specification: Title 47 CFR Part 15 and ICES-003

Prepared by EMI Test Lab - EmiTestLab.com

Model Name of EUT: TAZ WORKHORSE

Manufacturer: Aleph Objects Inc.

Revision 1.0

Electro Magnetic Interference Testing
EmiTestLab.com

Amplifier Research .800 – 4.2 GHz Amp	Radiated Immunity – 1 GHz to 2.7 GHz	10S1G4	34516	4 May 2020
Antenna Research Associates – 100 Watt amplifier w/controller	Radiated Immunity – 80- 1000 MHz in the FAR	ARAPS/PC757LC ARA757LC-CE	587V7 587V7	20 October 2019
Kalmus Power Amplifier	Radiated Immunity 150kHz – 1 GHz – in the GTEM	747LC-CE	7894-1	12 May 2020
Amplifier Research E- Field Probe	Radiated Immunity	FP 2000	12845	12 May 2020
Com-Power LISN	Conducted emissions	LI-115	241010	17 May 2020
Com-Power LISN	Conducted emissions	LI-115	241011	17 May 2020
California Instruments 1000 VA Power Source	Emissions and Immunity - used as a 100/120/230/240-VAC 50/60 Hz AC source	1001WP	L04788	4 June 2020
EMI Labs CDN	Conducted Immunity	EMICDN	001	9 Dec 2019
Hafely ESD Gun	Electro Static Discharge	ONYX16	181726	24 June 2020
KeyTek ECAT	Fast transients / Burst	E412	32612	5 June 2020
FCC Inc. RF Current Probe	Monitor Conducted Immunity signal	F-33-1	423	9 Dec 2019
EMI Labs Mag Loop	Magnetic Loop Antenna	Mag100	80162	12 Dec 2019
Thermo Keytek CE Master	Surge/ AC Dips and Interrupts	CE Master	0405277	15 Dec 2019
Audio Frequency Helmholtz Coil – Tektronix Audio Signal Generator and Audio Amplifier Test System	50 Hz to 10 kHz Magnetic field, homogenous – Immunity test	Audio Magnetic Field Test System	EMI-HH001	20 August 2020

6.0 Measurement Uncertainty - Radiated Emissions example;

Table of Uncertainty Calculation					
√	Contribution	Designation	Probability Distribution	k	Uncertainty (dB)
	Equipment Under Test Uncertainties	U_{EUT}			Note 1
√	Measuring Receiver Amplitude Accuracy	$U_{RXaccuracy}$	rectangular	$\sqrt{3}$	± 0.9
√	GTEM Uniformity	$U_{Uniformity}$	rectangular	$\sqrt{3}$	± 4.0
√	Secondary Field Components	$U_{Secondary}$			Excluded by Test Method
√	Mismatch Uncertainty-GTEM to Pre-Amplifier	$U_{Mismatch}$	U-shaped	$\sqrt{2}$	+0.63 and -0.65
√	Mismatch Uncertainty-Pre-Amplifier to Spectrum Analyzer	$U_{Mismatch}$	U-shaped	$\sqrt{2}$	+0.92 and -1.03
√	System Sensitivity Error	$U_{Sensitivity}$	rectangular	$\sqrt{3}$	0.28
√	GTEM Electric-Field Frequency Response	$U_{E-Field}$	rectangular	$\sqrt{3}$	± 1.6
	Ambient Signal Uncertainty	U_{Abient}			Not Significant
√	GTEM to OATS Correlation	U_{Corr}	rectangular	$\sqrt{3}$	±1.2
√	Septum Height Variation	U_{Septum}	normal	2	+0.72 and -0.82
	Coaxial Cable Temperature Variations	$U_{CableTemperature}$			Not Significant
√	Coaxial Cable Calibration	$U_{CableCalibration}$	rectangular	$\sqrt{3}$	±0.05
√	Pre-amplifier Calibration Uncertainty	$U_{Pre-Amp}$	rectangular	$\sqrt{3}$	±0.05
	Combined Uncertainty(dB) Positive Terms				2.77
	Combined Uncertainty(dB) Negative Terms				-2.75
	Expanded Uncertainty Positive Terms		Normal	2	5.54
	Expanded Uncertainty Negative Terms		Normal	2	-5.50

Typical Measurement Uncertainty for the following Tests:

The estimated combined standard uncertainty for Conducted Emissions is $\pm 1.2\text{dB}$
The estimated combined standard uncertainty for Radiated Immunity, EN 61000-4-3 is $\pm 2.7\text{dB}$
The estimated combined standard uncertainty for EFT/Burst, EN 61000-4-4 is $\pm 5.8\%$
The estimated combined standard uncertainty for Surge, EN 61000-4-5 is $\pm 8\%$
The estimated combined standard uncertainty for Conducted Immunity, EN 61000-4-6 is $\pm 1.5\text{ dB}$
The estimated combined standard uncertainty for Magnetic Fields, EN 61000-4-8 is $\pm 0.6\%$
The estimated combined standard uncertainty for Voltage Dips and Interrupts, EN 61000-4-11 is $\pm 4.3\%$
The estimated combined standard uncertainty for Harmonic current and flicker is $\pm 11.6\%$
The estimated combined standard uncertainty for ESD testing, EN 61000-4-2 is $\pm 4\%$

7.0 Test Plan

Testing required

The LulzBot TAZ WORKHORSE 3D Printer will be tested for Radiated and Conducted emissions, Harmonics and Flicker and all applicable Immunity tests as required for the EMC portion of the CE Mark and the Australia / New Zealand EMC standards. Previous power supply testing may be used as applicable.

Test Setup

The TAZ WORKHORSE will be operating using test software during all the testing.

The test software will be installed on a usb thumb drive, the program will be loaded from this drive.

The Printer will also be tested while connected and operated from a laptop through the usb cable supplied with the unit.

Failure Criteria

If the unit stops working or the printing process is altered by the injected noise, this would be considered a failure.

I/O cables

The unit has only one I/O cable, the USB cable that is used to control the printer from software installed on the host computer. There are no I/O cables on the unit 3 meters or longer.

Status of the test unit

Beta build.

8.0 Conclusion

The Aleph Objects – TAZ Workhorse 3D Printer complies with the emissions standards:

1. FCC Part 15 Class B for home or commercial use and
2. Industry Canada's ICES-003 Class B, also for home or commercial use.

in the configurations and operating modes as stated in this test report.

End of Report